

United States Patent and Trademark Office

UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

APPLICATION NO	.]	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/717,624		11/21/2003	Richard Ullyott	2993-484US CMB/al	8610
32292	7590	07/29/2005		EXAM	INER
		LT LLP (PWC) LEGE AVENUE		KIM, TA	AE JUN
SUITE 160		BEGETTVEROE		ART UNIT	PAPER NUMBER
MONTRE	AL, QC	H3A 2Y3		3746	
CANADA			DATE MAILED: 07/29/2009	DATE MAILED: 07/29/2005	

Please find below and/or attached an Office communication concerning this application or proceeding.

	Application No.	Applicant(s)
Office Action Summary	10/717,624	ULLYOTT, RICHARD
Onice Action Summary	Examiner	Art Unit
	Ted Kim	3746
The MAILING DATE of this communication app Period for Reply	ears on the cover sheet with the c	orrespondence address
A SHORTENED STATUTORY PERIOD FOR REPLY THE MAILING DATE OF THIS COMMUNICATION. - Extensions of time may be available under the provisions of 37 CFR 1.13 after SIX (6) MONTHS from the mailing date of this communication. - If the period for reply specified above is less than thirty (30) days, a reply - If NO period for reply is specified above, the maximum statutory period was really reply received by the Office later than three months after the mailing earned patent term adjustment. See 37 CFR 1.704(b).	36(a). In no event, however, may a reply be tim within the statutory minimum of thirty (30) days will apply and will expire SIX (6) MONTHS from cause the application to become ABANDONE	ely filed s will be considered timely. the mailing date of this communication. O (35 U.S.C. § 133).
Status		
1) Responsive to communication(s) filed on	<u>_</u> :	
2a) This action is FINAL . 2b) ⊠ This	action is non-final.	
3)☐ Since this application is in condition for allowar	· · · · · · · · · · · · · · · · · · ·	
closed in accordance with the practice under E	x parte Quayle, 1935 C.D. 11, 45	3 O.G. 213.
Disposition of Claims		
4) ☐ Claim(s) 1-22 is/are pending in the application. 4a) Of the above claim(s) is/are withdray 5) ☐ Claim(s) is/are allowed. 6) ☐ Claim(s) 1-22 is/are rejected. 7) ☐ Claim(s) is/are objected to. 8) ☐ Claim(s) are subject to restriction and/or	vn from consideration.	
Application Papers		
9) The specification is objected to by the Examine 10) The drawing(s) filed on is/are: a) access applicant may not request that any objection to the Replacement drawing sheet(s) including the correct 11) The oath or declaration is objected to by the Examine	epted or b) objected to by the Eddrawing(s) be held in abeyance. See ion is required if the drawing(s) is obj	37 CFR 1.85(a). ected to. See 37 CFR 1.121(d).
Priority under 35 U.S.C. § 119		
12) Acknowledgment is made of a claim for foreign a) All b) Some * c) None of: 1. Certified copies of the priority documents 2. Certified copies of the priority documents 3. Copies of the certified copies of the prior application from the International Bureau * See the attached detailed Office action for a list of	s have been received. s have been received in Application ity documents have been receive (PCT Rule 17.2(a)).	on No d in this National Stage
Attachment(s)		
1) Notice of References Cited (PTO-892) 2) Notice of Draftsperson's Patent Drawing Review (PTO-948) 3) Information Disclosure Statement(s) (PTO-1449 or PTO/SB/08) Paper No(s)/Mail Date 3/24/05 11/21/03. S. Patent and Trademark Office.	4) Interview Summary (Paper No(s)/Mail Dai 5) Notice of Informal Pa 6) Other:	e

Application/Control Number: 10/717,624 Page 2

Art Unit: 3746

DETAILED ACTION

Specification

1. The disclosure is objected to because of the following informalities: page 7, line 16, "172" appears it should be -174--.

Appropriate correction is required.

Claim Rejections - 35 USC § 102

2. The following is a quotation of the appropriate paragraphs of 35 U.S.C. 102 that form the basis for the rejections under this section made in this Office action:

A person shall be entitled to a patent unless -

- (b) the invention was patented or described in a printed publication in this or a foreign country or in public use or on sale in this country, more than one year prior to the date of application for patent in the United States.
- (e) the invention was described in (1) an application for patent, published under section 122(b), by another filed in the United States before the invention by the applicant for patent or (2) a patent granted on an application for patent by another filed in the United States before the invention by the applicant for patent, except that an international application filed under the treaty defined in section 351(a) shall have the effects for purposes of this subsection of an application filed in the United States only if the international application designated the United States and was published under Article 21(2) of such treaty in the English language.
- 3. Claims 1-6, 8, 9, 11-17, 19, 20, 22 are rejected under 35 U.S.C. 102(b) as being anticipated by Pellow (5,772,400). Pellow teaches in a gas turbine engine, a method for controlling a gap between a rotor blade tip and a turbine shroud, said method comprising: determining a cooling air requirement for said shroud; and controlling admission of cooling air to said turbine shroud area by adjusting a duty cycle of a modulating signal (col. 3, lines 8+) according to said cooling air requirement; a valve 70 controlling an air passage for said cooling air and wherein said controlling admission of cooling air comprises controlling said valve; said valve is positionable in one of a fully open (on)

position, when maximal air cooling results, and a fully closed (off) position, when no air cooling results; the valve control unit uses a signal representative an operating condition of said gas turbine engine for controlling said valve (e.g. throttle, fuel flow or other aircraft control demand); said modulating signal determines the position of said valve; said duty cycle comprises a light cooling mode and heavy cooling mode, wherein less cooling air is provided to the turbine area in said light cooling mode than in said heavy cooling mode. As for said operating condition is dependent on at least one of an aircraft cycle condition of said gas turbine selected from the group consisting of start; take-off, run-up, landing, normal cruise, low-level cruise, high-level cruise, low speed cruise, high speed cruise, reverse thrust, climb and descent, applicant lists all the known operating conditions of the engine, and the control signal will inherently be taken at one of these operation conditions.

4. Claims 1-6, 8, 9, 11-17, 19, 20, 22 are rejected under 35 U.S.C. 102(b) as being anticipated by Redinger, Jr. et al (4,069,662). Redinger, Jr et al teach in a gas turbine engine, a method for controlling a gap between a rotor blade tip and a turbine shroud, said method comprising: determining a cooling air requirement for said shroud; and controlling admission of cooling air to said turbine shroud area by adjusting a duty cycle of a modulating signal according to said cooling air requirement (col. 4, lines 12+); a valve 44 controlling an air passage for said cooling air and wherein said controlling admission of cooling air comprises controlling said valve; said valve is positionable in one of a fully open (on) position, when maximal air cooling results, and a fully closed

Application/Control Number: 10/717,624

Art Unit: 3746

Page 4

(off) position, when no air cooling results; the valve control unit uses a signal representative an operating condition of said gas turbine engine for controlling said valve; said modulating signal determines the position of said valve; said duty cycle comprises a light cooling mode and heavy cooling mode, wherein less cooling air is provided to the turbine area in said light cooling mode than in said heavy cooling mode. As for said operating condition is dependent on at least one of an aircraft cycle condition of said gas turbine selected from the group consisting of start; take-off, run-up, landing, normal cruise, low-level cruise, high-level cruise, low speed cruise, high speed cruise, reverse thrust, climb and descent, applicant lists all the known operating conditions of the engine, and the control signal will inherently be taken at one of these operation conditions, note the system is not turned on when on the ground (col. 4, lines 40+).

Claim Rejections - 35 USC § 103

- 5. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:
 - (a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.
- 6. Claims 1-22 are rejected under 35 U.S.C. 103(a) as being unpatentable over Redinger, Jr. et al (4,069,662) in view of any of Falk (3,421,318), McArthur (6,209,309) and Nystrom (3,999,388). Redinger, Jr et al teach various aspects of the claimed invention including modulating the on-off valve but does not specifically teach a PWM

valve. Falk teaches modulating flows with a PWM valve with a duty cycle (col. 1, lines 11+) is old and well known in the art. McArthur teaches using a PWM valve with a duty cycle is well known for its metering ability and low costs. Nystrom teaches using a PWM with a duty cycle solenoid controlled valve 37 to modulate a gas flow is old and well known in the art. It would have been obvious to one of ordinary skill in the art to employ a PWM valve with a duty cycle for the on-off control of the clearance control air, due to its low costs and/or flow modulating abilities and/or precise metering abilities. As for the duty cycles being between 0-50% in light cooling and 50-100% in heavy cooling, this is well known in the art as an obvious matter of using the workable ranges in the art. It would have been obvious to one of ordinary skill in the art to employ the claimed ranges as an obvious matter of finding the workable ranges in the art.

7. Claims 1-22 are rejected under 35 U.S.C. 103(a) as being unpatentable over Pellow (5,772,400) in view of any of Falk (3,421,318), McArthur (6,209,309) and Nystrom (3,999,388). Pellow teaches various aspects of the claimed invention including modulating the on-off valve but does not specifically teach a PWM valve. Falk teaches modulating flows with a PWM valve with a duty cycle (col. 1, lines 11+) is old and well known in the art. McArthur teaches using a PWM valve with a duty cycle is well known for its metering ability and low costs. Nystrom teaches using a PWM with a duty cycle solenoid controlled valve 37 to modulate a gas flow is old and well known in the art. It would have been obvious to one of ordinary skill in the art to employ a PWM valve with a duty cycle for the on-off control of the clearance control air, due to its low costs and/or

flow modulating abilities and/or precise metering abilities. As for the duty cycles being between 0-50% in light cooling and 50-100% in heavy cooling, this is well known in the art as an obvious matter of using the workable ranges in the art. It would have been obvious to one of ordinary skill in the art to employ the claimed ranges as an obvious matter of finding the workable ranges in the art.

8. Claims 1-22 are rejected under 35 U.S.C. 103(a) as being unpatentable over Franconi et al (6,910,851) in view of any of Falk (3,421,318), McArthur (6,209,309) and Nystrom (3,999,388). Franconi et al teach in a gas turbine engine, a method for controlling a gap between a rotor blade tip and a turbine shroud, said method comprising: determining a cooling air requirement for said shroud; and controlling admission of cooling air to said turbine shroud area by adjusting a modulating signal according to said cooling air requirement (col. 7, lines 62+); a valve 302 controlling an air passage for said cooling air and wherein said controlling admission of cooling air comprises controlling said valve; said valve is positionable in one of a fully open (on) position, when maximal air cooling results, and a fully closed (off) position, when no air cooling results; the valve control unit 354 uses a signal representative an operating condition of said gas turbine engine for controlling said valve; said modulating signal determines the position of said valve; said duty cycle comprises a light cooling mode and heavy cooling mode, wherein less cooling air is provided to the turbine area in said light cooling mode than in said heavy cooling mode; said operating condition is dependent on at least one of an aircraft cycle condition of said gas turbine selected from the group consisting of start, take-off.

run-up, landing, normal cruise, low-level cruise, high-level cruise, low speed cruise, high speed cruise, reverse thrust, climb and descent (see col. 7, lines 62+; col. 8, lines 4+). The valve is a solenoid valve and as such would appear to inherently have a duty cycle. Alternately, Falk teaches modulating flows with a PWM valve with a duty cycle (col. 1, lines 11+) is old and well known in the art. McArthur teaches using a PWM valve with a duty cycle is well known for its metering ability and low costs. Nystrom teaches using a PWM with a duty cycle solenoid controlled valve 37 to modulate a gas flow is old and well known in the art. It would have been obvious to one of ordinary skill in the art to employ a PWM valve with a duty cycle for the on-off control of the clearance control air, due to its low costs and/or flow modulating abilities and/or precise metering abilities. As for the duty cycles being between 0-50% in light cooling and 50-100% in heavy cooling. this is well known in the art as an obvious matter of using the workable ranges in the art. It would have been obvious to one of ordinary skill in the art to employ the claimed ranges as an obvious matter of finding the workable ranges in the art.

9. Claims 1-22 are rejected under 35 U.S.C. 103(a) as being unpatentable over JP 58-214603 in view of any of Falk (3,421,318), McArthur (6,209,309) and Nystrom (3,999,388). JP '603 teaches in a gas turbine engine, a method for controlling a gap between a rotor blade tip and a turbine shroud, said method comprising: determining a cooling air requirement for said shroud; and controlling admission of cooling air to said turbine shroud area by adjusting a modulating signal according to said cooling air requirement; a valve 16c-1, 16c-2, 16t-1, 16t-2 controlling an air passage for said cooling

air and wherein said controlling admission of cooling air comprises controlling said valve; said valve is positionable in one of a fully open (on) position, when maximal air cooling results, and a fully closed (off) position, when no air cooling results; the valve control unit 20 uses a signal representative an operating condition of said gas turbine engine for controlling said valve; said modulating signal determines the position of said valve; said duty cycle comprises a light cooling mode and heavy cooling mode, wherein less cooling air is provided to the turbine area in said light cooling mode than in said heavy cooling mode. The valve is a solenoid valve and as such would appear to inherently have a duty cycle. Alternately, Falk teaches modulating flows with a PWM valve with a duty cycle (col. 1, lines 11+) is old and well known in the art. McArthur teaches using a PWM valve with a duty cycle is well known for its metering ability and low costs. Nystrom teaches using a PWM with a duty cycle solenoid controlled valve 37 to modulate a gas flow is old and well known in the art. It would have been obvious to one of ordinary skill in the art to employ a PWM valve with a duty cycle for the on-off control of the clearance control air, due to its low costs and/or flow modulating abilities and/or precise metering abilities. As for the duty cycles being between 0-50% in light cooling and 50-100% in heavy cooling, this is well known in the art as an obvious matter of using the workable ranges in the art. It would have been obvious to one of ordinary skill in the art to employ the claimed ranges as an obvious matter of finding the workable ranges in the art.

~~~

### Contact Information

Any inquiry concerning this communication or earlier communications from the Examiner should be directed to Ted Kim whose telephone number is 571-272-4829. The Examiner can be reached on regular business hours before 5:00 pm, Monday to Thursday and every other Friday.

The fax numbers for the organization where this application is assigned are 571-273-8300 for Regular faxes and 571-273-8300 for After Final faxes.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's

supervisor, Timothy Thorpe, can be reached at 571-272-4444.

Any inquiry of a general nature or relating to the status of this application or proceeding should be directed to the receptionist of Technology Center 3700, whose telephone number is 703-308-0861. General inquiries can also be directed to the Patents Assistance Center whose telephone number is 800-786-9199. Furthermore, a variety of online resources are available at http://www.uspto.gov/main/patents.htm

| Ted Kim                             | Telephone         | 571-272-4829 |
|-------------------------------------|-------------------|--------------|
| Primary Examiner                    | Fax (Regular)     | 571-273-8300 |
| July 25, 2005                       | Fax (After Final) | 571-273-8300 |
| Technology Center 3700 Receptionist | Telephone         | 703-308-0861 |
| Patents Assistance Center           | Telephone         | 800-786-9199 |